

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: NuCaulk Colored Acrylic Sealant  
Recommended Use(s): Caulk, sealant  
Non-Recommended Use(s): Not specified  
Manufacturer: TOWER SEALANTS  
2095 Memorial Park Road, Gainesville, GA 30504  
Email: info@nugrout.com  
Url: www.nugrout.com  
Emergency Contact: Chemtrec 800424-9300 (within the USA), 202-483-7616 (outside of the USA)

## SECTION 2. HAZARD IDENTIFICATION

**Signal Words:** Danger

### Hazard Symbols



### Hazard Statements

H320 May cause eye irritation  
H350 May cause cancer  
H340 May cause genetic defects  
H372 May cause damage to organs through prolonged exposure

### Precautionary Statements

**General** P101 + P102 + P103 If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.

**Prevention** P201 + P202 + P260 + P281 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapor. Use personal protective equipment as required.

**Response** P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.  
P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician. P314 Get medical advice/ attention if you feel unwell.

**Storage** P405 Store locked up.

**Disposal** Dispose of contents/container in accordance with local regulations.

### HMIS Codes

Health: 2 \*  
Flammability: 1  
Physical Hazards: 0

\* Chronic effects

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

## SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Component / Occupational Exposure Limits	CAS No.	% By Weight
Limestone	1317-65-3	10-30
White mineral oil (petroleum)	8042-47-5	1-5
Ethylene Glycol	107-21-1	0.5-1.5
Titanium Dioxide	13463-67-7	0.5-1.5
Crystalline Silica, respirable powder (<10 microns)	14808-60-7	0.1-1

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4. FIRST-AID MEASURES

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

<b>INHALATION:</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult provide artificial respiration or oxygen by trained personnel. Get medical attention.
<b>SKIN CONTACT:</b>	Remove and wash contaminated clothing before re-use. Wash off immediately with soap and plenty of water. If irritation occurs, seek medical attention. DO NOT use solvents or thinners.
<b>EYE CONTACT:</b>	In case of eye contact, flush the eyes with water for 15 minutes. If contact lenses are worn, quickly remove them then flush the eyes with plenty of water. If irritation persists, have a physician examine the eyes.
<b>INGESTION:</b>	Seek immediate medical attention and show this container or label. Do not induce vomiting. If vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs.

### MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

#### Potential acute health effects

<b>INHALATION:</b>	May cause slight irritation to respiratory passages - headache - dizziness.
<b>SKIN CONTACT:</b>	May cause allergic skin reactions and / or central nervous system depression. May cause skin dryness and irritation.
<b>EYE CONTACT:</b>	Direct contact may cause slight to moderate irritation.
<b>INGESTION:</b>	Low ingestion hazard in normal use.

#### Over-exposure signs/symptoms

<b>INHALATION:</b>	No specific data.
<b>SKIN CONTACT:</b>	Adverse symptoms may include the following: irritation, dryness, cracking.
<b>EYE CONTACT:</b>	No specific data.
<b>INGESTION:</b>	No specific data.

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

---

**Indication of immediate medical attention and special treatment needed, if necessary**

**NOTES TO PHYSICIAN:** Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**SPECIFIC TREATMENTS:** No specific treatment.

**PROTECTION OF FIRST AIDERS:** No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

## SECTION 5. FIREFIGHTING MEASURES

**FLASH POINT:** N/A

**METHOD USED:** N/A

**EXPOSURE LIMITS:**

Lower (LEL): No Data Found

Upper (UEL): No Data Found

**FLAMMABILITY:** N/A

**CLASSIFICATION:**

**EXTINGUISHING MEDIA:** Use an extinguishing agent suitable for the surrounding fire.

**SPECIFIC HAZARDS:** In a fire or if heated, a pressure increase will occur, and the container may burst. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**HAZARDOUS THERMAL DECOMPOSITION PRODUCTS:** Decomposition products may include the following materials: carbon dioxide, carbon monoxide; metal oxide/oxides

**SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS:** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- NON-EMERGENCY PERSONNEL:** No action shall be taken involving any personal risk or without suitable training.
- Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist.
- Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- EMERGENCY RESPONDERS:** If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".
- ENVIRONMENTAL PRECAUTIONS:** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- METHODS FOR CLEANUP:**
- Small Spill:** Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large Spill:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## SECTION 7. HANDLING AND STORAGE

- PROTECTIVE MEASURES:** Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- SPECIAL PRECAUTIONS:** If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- ADVICE ON GENERAL OCCUPATIONAL HYGIENE:** Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:** Do not store below the following temperature: 5°C ( 41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

## SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMITS:

Chemical Name	ACGIH TLV	OSHA PEL / PEL Z3
Limestone	N.E.	TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
White mineral oil (petroleum)	N.E.	N.E.
Ethylene Glycol	TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable	TWA: 5 mg/m <sup>3</sup> 8 hours.
Titanium Dioxide	TWA: 10 mg/m <sup>3</sup> 8 hours.	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
Crystalline Silica, respirable powder (<10 microns)	TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form: Respirable	TWA: 10 MG/M3/(%SiO <sub>2</sub> +2) Form: Respirable TWA: 250 MPPCF / (%SiO <sub>2</sub> +5) 8 hours. Form: Respirable

### Key to Abbreviations

A = Acceptable Maximum Peak

ACGIH = American Conference of Governmental Industrial Hygienists.

C = Ceiling Limit

F = Fume

IPEL = Internal Permissible Exposure Limit

OSHA = Occupational Safety and Health Administration.

R = Respirable

Z = OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

S = Potential skin absorption

SR = Respiratory sensitization

SS = Skin sensitization

STEL = Short term Exposure limit values

TD = Total dust

TLV = Threshold Limit Value

TWA = Time Weighted Average

### Consult local authorities for acceptable exposure limits.

#### RECOMMENDED MONITORING PROCEDURES:

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### APPROPRIATE ENGINEERING CONTROLS:

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### ENVIRONMENTAL EXPOSURE CONTROLS:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

##### HYGIENE MEASURES:

Wash hands, forearms, and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

##### EYE/FACE PROTECTION:

Safety glasses with side shields.

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

<b>HAND PROTECTION:</b>	Chemical-resistant, impervious gloves complying with an approved standard should be always worn when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
<b>BODY PROTECTION:</b>	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>OTHER SKIN PROTECTION:</b>	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>RESPIRATORY PROTECTION:</b>	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state .....	Paste
Color .....	Various
Odor.....	Mild acrylic
Odor threshold .....	N/A
pH .....	7.5-8.5
Melting point.....	N/A
Boiling point .....	>37.78°C (>100°F)
Flash point.....	Closed cup: 93.89°C (201°F)
Auto-ignition temperature.....	N/A
Decomposition temperature.....	N/A
Flammability (solid, gas) .....	N/A
Lower and upper explosive (flammable) limits .....	N/A
Evaporation rate .....	0.31 (butyl acetate = 1)
Vapor pressure .....	2.3 kPa (17 mm Hg) [room temperature]
Vapor density.....	N/A
Relative density.....	1.16
Density (lbs/gal) .....	9.68
Solubility .....	Soluble in Water
Partition coefficient noctanol/water.....	N/A
Viscosity .....	15-40 g/s
Volatility .....	35% (v/v), 31% (w/w)
% Solid (w/w).....	69

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

## SECTION 10. CHEMICAL STABILITY AND REACTIVITY INFORMATION

<b>REACTIVITY:</b>	No specific test data related to reactivity available for this product or its ingredients.
<b>CHEMICAL STABILITY:</b>	The product is stable.
<b>POSSIBILITY OF HAZARDOUS REACTIONS:</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>CONDITIONS TO AVOID:</b>	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
<b>INCOMPATIBLE MATERIALS:</b>	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

## SECTION 11. TOXICOLOGICAL INFORMATION

<b>ACUTE TOXICITY:</b>	<b>Ingredient</b>	<b>Oral LD50</b>	<b>Dermal LD50</b>	<b>Inhalation LC50</b>
	White mineral oil (petroleum)	5000 mg/kg (Rat)		
	Ethylene Glycol	4700 g/kg (Rat)	9.53 g/kg (Rabbit)	
	Titanium Dioxide	> 10 g/kg (Rat)		

**Conclusion/Summary:** There are no data available on the mixture itself.

### IRRITATION/CORROSION:

**Conclusion/Summary:**

<b>SKIN:</b>	There are no data available on the mixture itself.
<b>EYES:</b>	There are no data available on the mixture itself.
<b>RESPIRATORY:</b>	There are no data available on the mixture itself.

### SENSITIZATION:

**Conclusion/Summary:**

<b>SKIN:</b>	There are no data available on the mixture itself.
<b>RESPIRATORY:</b>	There are no data available on the mixture itself.

### MUTAGENICITY:

**Conclusion/Summary:** There are no data available on the mixture itself.

### CARCINOGENICITY:

**Conclusion/Summary:** There are no data available on the mixture itself.

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

CLASSIFICATION:	Ingredient	IARC	NTP	OSHA
	Titanium Dioxide	2B - Possible Human Carcinogen		
	Crystalline Silica, respirable powder (<10 microns)	1 - Carcinogenic to Humans	Known to be a human carcinogen.	

Carcinogen Classification code:  
IARC: 1, 2A, 2B, 3, 4  
NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen  
OSHA: +  
Not listed/not regulated: -

## REPRODUCTIVE TOXICITY:

**Conclusion/Summary:** There are no data available on the mixture itself.

## TERATOGENICITY:

**Conclusion/Summary:** There are no data available on the mixture itself.

**SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE):** Not available.

## SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE):

Name	Category
Ethylene Glycol	Category 2
Crystalline Silica, respirable powder (<10 microns)	Category 2

## TARGET ORGANS:

Contains material which may cause damage to the following organs: kidneys, lungs, heart, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

## ASPIRATION HAZARD:

Name	Category
White mineral oil (petroleum)	ASPIRATION HAZARD Category 1

## INFORMATION ON THE LIKELY ROUTES OF EXPOSURE:

### Potential acute health effects:

- EYE CONTACT:** Direct contact may cause slight to moderate irritation.
- INHALATION:** May cause slight irritation to respiratory passages - headache - dizziness.
- SKIN CONTACT:** May cause allergic skin reactions and / or central nervous system depression. May cause skin dryness and irritation.
- INGESTION:** Low ingestion hazard in normal use.

### Over-exposure signs/symptoms:

- EYE CONTACT:** No specific data.
- INHALATION:** No specific data.
- SKIN CONTACT:** Adverse symptoms may include the following: irritation, dryness, cracking
- INGESTION:** No specific data.



# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

## Delayed and immediate effects and chronic effects from short- and long-term exposure:

### Conclusion/Summary:

There are no data available on the mixture itself. This product contains Crystalline Silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Sort term exposure:

#### POTENTIAL IMMEDIATE EFFECTS:

There are no data available on the mixture itself.

#### POTENTIAL DELAYED EFFECTS:

There are no data available on the mixture itself.

### Long term exposure:

#### POTENTIAL IMMEDIATE EFFECTS:

There are no data available on the mixture itself.

#### POTENTIAL DELAYED EFFECTS:

There are no data available on the mixture itself.

### Potential chronic health effects:

#### GENERAL:

May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

#### CARCINOGENICITY:

May cause cancer. Risk of cancer depends on duration and level of exposure.

#### MUTAGENICITY:

No known significant effects or critical hazards.

#### TERTOGENICITY:

No known significant effects or critical hazards.

#### DEVELOPMENTAL EFFECTS:

No known significant effects or critical hazards.

#### FERTILITY EFFECTS:

No known significant effects or critical hazards.

### Numerical measures of toxicity:

#### ACUTE TOXICITY ESTIMATES:

Route	ATE Value
Oral	14103.8 mg/kg

## SECTION 12. ECOLOGICAL INFORMATION

### Toxicity

Product / ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute EC50 100 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours

### Persistence and degradability

Not Available.

### Bioaccumulative potential

Product / ingredient name	LogPow	BCF	Potential
White mineral oil (petroleum)	>6	-	High
Ethylene Glycol	-1.36	-	Low

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>): Not available.

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

## SECTION 13. DISPOSAL CONSIDERATIONS

**METHOD:** The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should always comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## SECTION 14. TRANSPORTATION INFORMATION [ADR-UN, DOT, ICAO, IMDG, TDGR]

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

	DOT	IMDG	IATA
UN number	UN3082	Not regulated.	Not regulated.
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (carbendazim (ISO))	-	-
Transport hazard class(es)	9	-	-
Packing group	III	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.
Product RQ (lbs)	14992.5	Not applicable.	Not applicable.
RQ substances	(carbendazim (ISO))	Not applicable.	Not applicable.

### Additional Information

**DOT** Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

**IMDG** None identified.

**IATA** None identified.

**Special precautions for user:** **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

## SECTION 15. REGULATORY INFORMATION

**United States inventory (TSCA 8b):** All components are listed or exempted.  
**Australia inventory (AICS):** Not determined.  
**Canada inventory (DSL):** All components are listed or exempted.  
**China inventory (IECSC):** Not determined.  
**Europe inventory (REACH):** Please contact your supplier for information on the inventory status of this material.  
**Japan inventory (ENCS):** Not determined.  
**Korea inventory (KECI):** Not determined.  
**New Zealand (NZIoC):** Not determined.  
**Philippines inventory (PICCS):** Not determined.

**SARA 302/304/304 RQ:** Not applicable.  
**Composition/information on ingredients:** No products were found.

**SARA 311/312:**  
**Classification:** Immediate (acute) health hazard  
 Delayed (chronic) health hazard

**Composition/information on ingredients:**

Name	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
White mineral oil (petroleum)	No	No	No	Yes	No
Ethylene Glycol	No	No	No	Yes	Yes
Titanium Dioxide	No	No	No	No	Yes
Crystalline Silica, respirable powder (<10 microns)	No	No	No	No	Yes

**SARA 313:** Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical(s) which are subject to the reporting requirements of the Act and 40 CFR Part 372:

CHEMICAL COMPONENT	CAS No.	Concentration
Ethylene Glycol	107-21-1	0.5 - 1.5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**PENNSYLVANIA (WORKER AND COMMUNITY RIGHT TO KNOW ACT):** The following components are cited in the Pennsylvania Hazardous Substances List and are present at levels that require reporting.  
**Ethylene Glycol 107-21-1 < 2%**

**CALIFORNIA PROPOSITION 65:** This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

**STATE RIGHT-TO-KNOW:**

Ingredient	Massachusetts	New Jersey	Pennsylvania
Titanium Dioxide	Listed	Listed	Listed

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012 and WHMIS 2015  
Product: NuCaulk Colored Acrylic Sealant



Revision Date: 2014-10-30

## SECTION 16. OTHER INFORMATION

### HMIS CODES

Health: 2 \*  
Flammability: 1  
Physical Hazards: 0

\* *Chronic effects*

**Caution:** HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

### NATIONAL FIRE PROTECTION ASSOCIATION

Health: 2 \*  
Flammability: 1  
Instability: 0

### Key to abbreviations:

ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations

### NON-WARRANTY:

The information presented in this publication is based upon the research and experience of Centura Paint. No representation or warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Centura Paint makes no warranty or representation of any kind, express or implied, including without limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Centura Paint are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. Centura Paint assumes no responsibility for the selection of products suitable to the particular purposes of any particular buyer. Centura Paint shall in no event be liable for any special, incidental, or consequential damages.

MSDS STATUS: Approved.  
REVISION DATE: 2014-10-30