



2. MANUFACTURER

Manufactured for NuGrout by:
CENTURA PAINT MANUFACTURING, INC.
4300 NW 1st Ave
Boca Raton, FL 33431
Phone: 1-800 NuGROUT (1-800-684-7688)
Email: info@nugrout.com

3. PRODUCT DESCRIPTION

NuCaulk™ Colored Acrylic Sealant is a color-matched, premium-quality, siliconized acrylic sealant that can be used to caulk around a wide range of surfaces in interior, exterior and wet areas. The product forms a flexible, durable, airtight, and water-resistant seal that offers protection from environmental conditions.

FEATURES

- Compatible with all types of tile and stone.
- Seal around sinks, countertops, showers, tub surrounds, windows, trim, doors, siding, penetrations, hardboard, flashing and more!
- Comes in 24 stylish standard colors.
- Available in most grout manufacturers colors.
- Custom color matching available.
- 100% Siliconized-acrylic formula.
- Excellent elongation and recovery.
- Easy to apply and clean.
- Solvent-free and low VOC.
- Inhibits the growth of mold and mildew.
- For interior and exterior use, and in wet areas.
- Meets or exceeds ASTM C834 Type OP, Grade-18C standards.

PACKAGING

10.1 fl oz (310 mL) tube

4. TECHNICAL DATA

Drying time	4-6 hours
Initial cure.....	24 hours
Time before exposure to water.....	48 hours
Final cure.....	72 hours
VOC content.....	< 2%
Clean up.....	Warm, soapy water

HANDLING AND STORAGE

- Always follow product safety guidelines during storage and use (reference product SDS for complete details).
- Seal nozzle after each use.
- Store product in original container only.
- Product shelf life is 36 months when unopened and stored at room temperature.
- Use only when surface temperatures are between 40° F - 120° F (4° C - 49° C).

APPROXIMATE COVERAGE

Approximately 50 linear feet for a 3/16" bead (15 m for a 4.5 mm bead)

4. INSTALLATION

MIXING

No mixing is required. This product is ready for use as is.

SURFACE PREPARATION

Thoroughly clean and all surfaces to be adhered to, removing all dust, dirt, soap-scum, contaminants and other deleterious materials.

APPLICATION

1. Cut nozzle at 45° angle, then apply bead with standard caulking gun, completely filling joint. If joint depth exceeds 1/4" (6 mm), use a foam backer rod. Joints should not exceed 1/2" (13 mm) depth.
2. Smooth with moistened finger or clean cloth.
3. Wipe away excess sealant with moistened finger or clean cloth soon after application.

CLEANING

Clean tools and hands with warm, soapy water after use.

HEALTH AND SAFETY

Reference product SDS for complete safety information.

6. AVAILABILITY AND COST

NuCaulk™ Colored Acrylic Sealant is available at select retail and commercial distribution locations throughout the United States and Canada, and on-line outlets, including www.nugrout.com. Costs may vary. Contact us for specific information.



7. WARRANTY

CENTURA PAINT MANUFACTURING warrants that this product is manufactured using quality raw materials and is of merchantable quality and suitable for the purpose for which it was intended. No other guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, or other consequential damages is hereby excluded.

8. MAINTENANCE

Proper maintenance and sanitation using household cleaners is still necessary. Avoid use of harsh chemicals and acids when cleaning.

9. TECHNICAL SERVICE

Please contact us at 1-800 NUGROUT (1-800-684-7688), for proper recommendations and job field assistance.

10. FILING SYSTEM

Additional information is available upon request, or by visiting www.nugrout.com.