


STEP 1 GATHER YOUR TOOLS

- NuGrout™ Application Tool (recommended), good-quality nylon brush or roller
- Rubber gloves and eye protection
- Clean sponge and rags
- Pail of warm soapy water



STEP 6 BRUSH COLORANT INTO GROUT

Spread colorant evenly onto grout surface using the NuGrout™ Application Tool or a good-quality nylon brush, working it deeply into the surface using a back-and-forth motion. For best results, apply in two coats (waiting 2-4 hours drying time between coats).



STEP 2 APPLY CLEANER AND PRETREAT

For best results, use NuGrout™ Cleaner and Pretreat to thoroughly clean and lightly etch all grout surfaces to be coated. Apply a bead of cleaner to the grout joint.



STEP 7 REMOVE EXCESS COLORANT

Use the convenient built-in squeegee, on the back of the NuGrout™ Application Tool to help remove excess product from tile and grout joints.



STEP 3 CLEAN GROUT

Using the NuGrout™ Application Tool, or a stiff nylon brush, scrub grout joint until clean. Add cleaner as needed. Remove all dust, dirt, grime, soap-scum, mold, contaminants and other deleterious materials.



STEP 8 CLEAN SURFACE

After 20 to 30 minutes drying time, remove the remaining excess product from the tile using a sponge or rag, being careful not to scrub the grout joint.

NuGrout™ Colorant and Sealer is ready for light foot traffic after only 2-4 hours, normal foot traffic after 24 hours, and heavy, commercial traffic after only 72 hours. Allow up to 72 hours drying time for areas subjected to high humidity.



STEP 4 REMOVE CLEANER RESIDUE

Thoroughly rinse grout joints with water, removing all residue. Use a clean sponge and the squeegee on the back of the NuGrout™ Application Tool to aid cleanup.



STEP 5 APPLY COLORANT

If using more than 1 bottle of a single color for an application, mix all material together in a larger container prior to use to ensure color is consistent. Apply a bead of colorant directly to grout joint.



STEP 9 REPLACE CAULK

Remove old caulk, thoroughly clean areas to be re-caulked, then apply NuCaulk™ Colored Acrylic Sealant (see Technical Data Sheet for instructions). Seal around sinks, countertops, showers, tub surrounds, windows, trim, doors, siding, penetrations, hardboard, flashing and more!