



2. MANUFACTURER

Manufactured for NuGrout by:
CENTURA PAINT MANUFACTURING, INC.
4300 NW 1st Ave
Boca Raton, FL 33431
Phone: 1-800 NUGROUT (1-800-684-7688)
Email: info@nugrout.com

3. PRODUCT DESCRIPTION

NuGrout™ Colorant and Sealer is a powerful, 100% acrylic colorant and sealer that penetrates deep into grout to add a fresh, new appearance that will renew the look of any tile installation. When dry, NuGrout Colorant and Sealer permanently seals grout to help protect its new brilliance against grime, stains, mold and mildew.

FEATURES

- Gives old tile areas a fresh, new appearance
- Change grout to any color you want
- Great for renewing grout that has become dull and dingy
- Use to correct color problems on a new grout installation
- Ideal for use on remodeling jobs
- Professional-quality results
- Comes in 24 stylish standard colors
- Available in most grout manufacturers colors
- Custom color matching available
- Powerful, 100% acrylic formula
- Easy to apply
- Cleans up with soap and water
- Stain-resistant seal
- Inhibits the growth of mold and mildew
- For interior or exterior use and in wet areas (not recommended for submerged applications, such as pools or fountains).

PACKAGING

8 fl oz (237 mL) bottle
1 US qt (946 mL) can
1 US gal (3,79 L) can
5 US gal (18.9 L) pail

NuGrout™ Recoloring Kit:
1 - 8 fl. oz (237 mL) bottle NuGrout™ Colorant and Sealer
1 - 8 fl. oz (237 mL) bottle NuGrout™ Cleaner and Pretreat
1 - NuGrout™ Application Tool
1 - cellulose sponge
1 - pair of latex gloves

4. TECHNICAL DATA

Drying time (tack-free) 30 min
Recoating.....2-4 hours
Final cure (normal traffic)..... 24 hours
Final cure (heavy traffic).....72 hours
Thinning..... Generally not required
Flash point..... Over 214° F
Clean up..... Warm, soapy water
Sheen..... Flat 10 at 60°

HANDLING AND STORAGE

- Always follow product safety guidelines during storage and use (reference product SDS for complete details).
- Use only when surface temperatures are between 50°F–90°F (10°C–32°C).
- Product shelf life is 36 months when unopened and stored at room temperature.
- Store product in original container only.
- Close cap on container after each use.

APPROXIMATE COVERAGE

Tile Size	Grout Joint Width		
	1/8" (3 mm)	3/16" (4.5 mm)	1/4" (6 mm)
1" x 1" (25 x 25 mm)	—	50 sq ft (4.7 m ²)	—
3" x 3" (75 x 75 mm)	—	85 sq ft (7.9 m ²)	—
4" x 4" (10 x 10 cm)	200 sq ft (18.6 m ²)	95 sq ft (8.8 m ²)	80 sq ft (7.4 m ²)
6" x 6" (15 x 15 cm)	225 sq ft (20.9 m ²)	110 sq ft (10.2 m ²)	95 sq ft (8.8 m ²)
8" x 8" (25 x 25 cm)	250 sq ft (23.2 m ²)	125 sq ft (11.6 m ²)	110 sq ft (10.2 m ²)
12" x 12" (33 x 33 cm)	300 sq ft (27.9 m ²)	145 sq ft (13.4 m ²)	125 sq ft (11.6 m ²)
16" x 16" (41 x 41 cm)	360 sq ft (33.4 m ²)	175 sq ft (16.3 m ²)	135 sq ft (12.5 m ²)

4. INSTALLATION

MIXING

No mixing is required. This product is ready for use as is, unless using more than 1 bottle of a single color for an application, then mix all material together in a larger container prior to use to ensure color is consistent.



SURFACE PREPARATION

Thoroughly clean and lightly etch all grout surfaces to be coated using *NuGrout™ Cleaner and Pretreat*, removing all dust, dirt, soap-scum, contaminants and other deleterious materials (reference Technical Data Sheet for complete details).

Sealing of porous tile may be required prior to application of grout colorant to ensure it is not absorbed into the tile.

APPLICATION

1. Spread colorant evenly onto grout surface using a good quality roller or brush, such as the *NuGrout™ Application Tool*, working it deeply into the surface using a back-and-forth motion.
2. Remove excess product from tile and grout joints.
3. After 30 minutes drying time (depending upon climate conditions), remove the remaining excess product from the tile using warm soapy water and a sponge or rag, being careful not to scrub the grout joint.
4. If there is only light staining and a small difference in color change, you may only need one coat of NuGrout Colorant and Sealer. For heavier-stained grout and/or a larger degree of color transformation, two or more coats may be necessary (waiting 2-4 hours drying time between coats). Test a small area prior to full application to determine your desired results.

CLEANING

Clean tools and hands with warm, soapy water after use.

HEALTH AND SAFETY

Reference product SDS for complete safety information.

6. AVAILABILITY AND COST

NuGrout™ Colorant and Sealer is available at select retail and commercial distribution locations throughout the United States and Canada, and on-line outlets, including www.nugrout.com. Costs may vary. Contact us for specific information.

7. WARRANTY

CENTURA PAINT MANUFACTURING warrants that this product is manufactured using quality raw materials and is of merchantable quality and suitable for the purpose for which it was intended. No other guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, or other consequential damages is hereby excluded.

8. MAINTENANCE

When properly applied, NuGrout™ Colorant and Sealer seals the grout joint to resist the penetration of stains, dirt and grime. Proper maintenance and sanitation using household cleaners is still necessary. Avoid use of harsh chemicals and acids when cleaning.

9. TECHNICAL SERVICE

Please contact us at 1-800 NUGROUT (1-800-684-7688), for proper recommendations and job field assistance.

10. FILING SYSTEM

Additional information is available upon request, or by visiting www.nugrout.com.